


|  |                                |   |               |
|--|--------------------------------|---|---------------|
| <b>A1. Model No.:</b>  |                                | <b>A2. Product Name:</b>  |               |
| ST-SV-HD135410CAI  |                                | HD CAMERA   |               |
| <b>B1. Product Keywords:</b>   |                                |  |               |
| 1) 720P<br>2) Waterproof: IP69K approved<br>3) Super wide viewing angle: 170°<br>4) Smart-IR         |                                |   |               |
| <b>B2. Product Features:</b>   |                                |   |               |
| 1) Nightvision distance: 3-5 m (5 infrared lights)<br>2) Day / Night sensor for automatic adjustment |                                |   |               |
| <b>B3. Key Specifications:</b>   |                                |   |               |
| Image Device:  | 1/3" SONY CMOS IMX225          |   |               |
| Frame Rate:  | 25 / 30 fps                    |   |               |
| Effective Pixels:  | 1280 (H) x 720 (V)             |   |               |
| Pixel pitch  | 3.75 μm x 3.75 μm              |   |               |
| Scanning System:   | Progressive Scanning           |   |               |
| Sync. System:  | Internal                       |   |               |
| Resolution:  | 720P                           |   |               |
| Minimum Illumination:  | 0.1 Lux (day), 0 Lux (with IR) |   |               |
| Microphone:  | Yes                            |   |               |
| Video Output:  | 1.0Vp-p, 75Ohm                 |   |               |
| Gamma Consumption:   | 0.45                           |   |               |
| AGC:   | Auto                           |   |               |
| White Balance:   | Auto                           |   |               |
| Electronic Shutter:  | 1/25 (1/30) ~ 1/50,000 Seconds |   |               |
| BLC:   | Auto                           |   |               |
| Current Consumption:   | Max. 220mA                     |   |               |
| Power Supply:  | DC 12 V                        |   |               |
| Connection:  | RCA / 4 PIN                    |   |               |
| Anti-vibration:  | 10 g                           |   |               |
| Operating Temperature:   | -20°C~70°C, RH 95% MAX.        |   |               |
| Lens:  | f = 1.78 mm                    |   |               |
| Lens Angle:  | 150° (Diagonal Degree)         |   |               |
| <b>C1. Accessories:</b>  |                                |   |               |
| 1- Manual  |                                |   |               |
| 1- Screwdriver   |                                |   |               |
| <b>D1. Packing:</b>  |                                |   |               |
| Weight Of Unit Product:  | 0.2 KG                         | Weight Of Export Carton:  | 11 KG         |
| Dimension Of Giftbox:  | 9.3*8.1*6.6 (CM)               | Dimension Of Export Carton:   | 44*43*21 (CM) |
| 20"/40"/40"HQ Qty:   |                                | Dimension Of Export Carton:   | 50 PCS        |
| <b>E1. Payment Term:</b>   |                                | <b>F1. Warranty Terms:</b>  |               |
| T/T or L/C at sight  |                                | 18 MONTHS warranty  |               |
| <b>G1. Certificates:</b>   |                                | <b>H1. Reference Price:</b>   |               |
|  |                                | Sample:   | USD 49.50     |
|  |                                | Lead time:  | 7 days        |
| <b>I1. Remarks:</b>  |                                |   |               |
|  |                                |   |               |