

AIR VUE™

WIRELESS THAT **ACTUALLY** WORKS

#CANCEL Blind Spots



No more hefty repair bills. No more heart-stopping near misses. Welcome to a new era of fleet safety and efficiency with the Air Vue™, a Blind-Spot-Canceling Wireless System.



Automatic Instant Pairing

Patent pending Pairing-Over-Power enables camera + monitor pairing via vehicle's electrical system.



Effortless Usage

No buttons to push- the operator doesn't have to do anything to activate the system!



Reliable Connection

Air Vue™ ensures accurate tractor-trailer pairing, even in crowded freight yards.



Easily Integrated

Seamlessly integrate IP69K front and side cameras. With this versatile system you can cover the blind spots and prevent side-swipes.



Strong Signal

300FT stable transmission range that covers even double and triple towing.



Telematics Services

Easily connect to platforms such as, Samsara, Lytx, and Netradyne



Speedy Installation

Get your whole fleet ready to hit the road quickly with minimal downtime.



Video Output

Supports SD Card recording Plus one independent CVBS video output

Your All-encompassing Wireless Solution



The **Air Vue™ Advanced** gives tractor trailer drivers a multitude of viewing options, with its 4-channel split views and the option to send the video feeds to external recorders. Each camera channel can be independently adjusted for horizontal-mirror or vertical-mirror view displays and supports a respective trigger line. Easy installation, adjustable parking lines and built in recorder.

Power supply	DC 10-32V
Video input	AHD720P / AHD1080P
Video Codec	H.264
Operation frequency	2400 - 2483.5 MHz (ISM band)
Modulation	QPSK
RF Bit Rate	6Mbps
Spread spectrum	FHSS
Transmitter Power	FCC < 26 dBm, CE < 20 dBm, MIC < 10 dBm
Receiving Sensitivity	-78dBm
Transmission Range	FCC < 300 m, CE < 200 m, MIC < 60 m
Active area	154.08(H) x 85.92(V) mm
Signal delay	< 200ms
Operating Temperature	-20 ~ +70°C RH90%
Storing Temperature	-30 ~ +80°C RH90%

